

Meshless methods for 'gas - evaporating droplet' flow modelling

Oyuna Rybdylova and Sergei S Sazhin

The Sir Harry Ricardo Laboratories, Advanced Engineering Centre,
School of Computing, Engineering and Mathematics, University of
Brighton, UK

Abstract

The main ideas of simulation of two-phase flows, based on a combination of the conventional Lagrangian method or fully Lagrangian method (FLM) for the dispersed phase and the mesh-free vortex and thermal blob methods for the carrier phase, are summarised. A meshless method for modelling of 2D transient, non-isothermal, gas-droplet flows with phase transitions, based on a combination of the viscous-vortex and thermal-blob methods for the carrier phase with the Lagrangian approach for the dispersed phase, is described. The one-way coupled, two-fluid approach is used in the analysis. The method makes it possible to avoid the 'remeshing' procedure (recalculation of flow parameters from Eulerian to Lagrangian grids) and reduces the problem to the solution of three systems of ordinary differential equations, describing the motion of viscous-vortex blobs, thermal blobs, and evaporating droplets. The gas velocity field is restored using the Biot-Savart integral. The numerical algorithm is verified against the analytical solution for a non-isothermal Lamb vortex. The method is applied to modelling of an impulse two-phase cold jet injected into a quiescent hot gas, taking into account droplet evaporation. Various flow patterns are obtained in the calculations, depending on the initial droplet size: (i) low-inertia droplets, evaporating at a higher rate, form ring-like structures and are accumulated only behind the vortex pair; (ii) large droplets move closer to the jet axis, with their sizes remaining almost unchanged; and (iii) intermediate-size droplets are accumulated in a curved band whose ends trail in the periphery behind the head of the cloud, with larger droplets being collected at the front of the two-phase region.